

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/029382 A1

(51) International Patent Classification⁷: **E04G 1/26**

(74) Agent: ALBIHNS GÖTEBORG AB; Box 142, S-401 22
Göteborg (SE).

(21) International Application Number:
PCT/SE2003/001502

(22) International Filing Date:
26 September 2003 (26.09.2003)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0202876-9 27 September 2002 (27.09.2002) SE

(71) Applicant (for all designated States except US): **PLU-
SEIGHT SAFETY AB** [SE/SE]; Box 10, S-430 63
Hindås (SE).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **WALLTHER, Harry**
[SE/SE]; Limmerhultsvägen 60, S-430 63 Hindås (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DEVICE FOR PERSONAL SAFETY ON SCAFFOLDS



(57) Abstract: The present invention relates to a device for personal safety on such scaffolds as consist of scaffold uprights (5, 6) and lying scaffold elements (64-73) coupled between the uprights. The safety device consists of two safety uprights (18, 19) and a guard rail (24) extending between the safety uprights. The safety uprights have coupling devices (20-23) for releasable coupling-together with the scaffold. The coupling devices interact with an upwardly facing portion of the scaffold. By means of the device, the safety uprights and the accompanying guard rail can be moved successively between different vertical positions according to safety requirements.

WO 2004/029382 A1